

Fish Tank Window Kit Instructions

What you'll need: drill, jigsaw and blades, ruler, wrench(s), silicone, rubbing alcohol, file, sandpaper, paper towels, 3" hole saw, marker

1. Place window in position - you can have someone help you hold it in place
 - a. Make sure the window is level
2. Drill holes and place bolts in as you drill, tightening nut on the other side
3. Remove screws and window
4. Draw cutline - should be 2 1/2" in from the outside edge of window
5. Prepare to drill circular holes in corner using a 3" hole saw/ jigsaw
6. Drill holes
7. Cut out window with a jigsaw
 - a. Make sure blade doesn't get hot enough to melt the plastic
8. File off plastic burrs
9. Sand down inside of tank between the window hole and the bolt holes
10. Clean all areas that were sanded with alcohol
11. Peel off protective backing from window
12. Apply silicone to window - inside and outside of bolt holes
13. Place window securely inside tank - make sure all bolt holes line up

14. Insert bolts into all holes applying silicone liberally to bolt
 - a. Start in the center and work out towards the corners
 - b. Make sure the bolt head is on the inside of the tank, and the nuts are on the outside
 - c. Tighten the nuts on each bolt fully
15. Apply silicone sealant to outside of tank around edge of window
16. Apply silicone sealant to inside of fish tank, around edge of window
17. Clean and smooth silicone sealant
 - a. Spray water on area to clean, and wipe silicone with finger

Wait 2 days for silicone to dry, fill your tank with water, add fish and enjoy!

Scan this code for our video instructions!

